

Installation manual	Model: Fe	ord Maverick Diz	Skid plate	for: engine bay	Article:	08.0368
Body type:R20, UDS, U	NS	Years: 02/1993-	04/1998	Engine type: 2.4i D,	2.7 D	

Engine bay and transmission elements skid plate has been designed and manufactured by LLC Metalloproduktsia. Product conforms to TOR 4591-001-25888788-2006 requirements. Product design is protected by model copyright certificates N89095, 15990. 15981, 15982, 15983. Patented in Russian Federation.

APPLICATION:

Protection of engine bay and transmission elements from mechanical deformation.

Protection of engine bay and transmission elements from dust and damp.

INSTALLATION:

Engine bay and transmission elements skid plate has been designed particularly for a certain vehicle. It should be mounted according to the producer's installation instruction by a declicated dealer or on certified service stations. The skid plate is fixed to regular apertures located on vehicle's body load-bearing elements. In case of correct installation the skid plate should not interfere with any vehicle's units and components.

INSTALLATION MANUAL:

Disassemble the skid plate to component parts.

- 2 Fix the beam of the skid plate under the OF neets on the cross har
- 3. Fix the cramps under the transmission's beam.
- A Place threated inserts into reductor's beam apertures.
- 5 Place part "A" to cramps fixed behind and fix in the front
- 6.Fix part "B" to the transport lugs and fix together with the part "A" behind.
 7. Fix part "C" to cramps in the front and to fixed threated inserts in the rear part.

8. Tighten all screw joints. OPERATING CONDITIONS:

Engine bay and transmission elements skid plate has been designed to operate in conditions specified by vehicle's producer. Cases of crush or driving into obstacles at a speed should be excluded during exploitation. In case of head-on crush it is necessary to assure in absence of damages of vehicle's components and units and availability of randworthiness, on certified service stations.

WARRANTY:

Warranty period - 1 year.

WARRANTY TERMS:

The skid plate should be installed on a vehicle with undamaged body and load-bearing elements (vehicle, which hads

never been involved in road traffic accident);
There are no mechanical damages of the skid plate resulting from head-on crush. All requirements to skid plate installation should be satisfied;


There are no mechanical damages of powder coating.

There are no mechanical damages of poweer coating.

Producer does not bear liability for damages caused to the vehicle, health and life of people in case of installation and exploitation terms violation. Producer has a right to introduce changes into the skid plate construction.



The Quality Management System of LLC Metalloproduktsia has been audited by Bureau Veritas Certification and conforms to requirements of the ISO 9001:2008 standard.





NO.	NAME	QTY.	NO.	NAME	QTY
1	Cramps	2	5	Bolt M 10x30	8
2	SD 2002	2	6		
3	Washer 10	11	7		
4	Bolt M 10x20	3	8		

24 ft HM

81 0 HM

Tightening torque