

Installation manual	Model: Mitsubishi Galant	Skid plate for: engine bay	Article: 14.0280
---------------------	--------------------------	----------------------------	------------------

3

threated incerte

Bolt M8x20

Body type: Years:1996- 2004 Engine type: 2.0, 2.4, 2.5, 2.0TDI

Engine bay and transmission elements skid plate has been designed and manufactured by LLC Metalloproduktsia. Product conforms to TOR 4591-001-25888788-2006 requirements. Product design is protected by model copyright certificates Nk99059, 15980, 15981, 15982, 15983. Patented in Russian Federation.

APPLICATION:

Protection of engine bay and transmission elements from mechanical deformation.

Protection of engine bay and transmission elements from dust and damp.

INSTALLATION:

Engine bay and transmission elements skid plate has been designed particularly for a certain vehicle. It should be mounted according to the producer's installation instruction by a dedicated dealer or no critified service stations. The skid plate is fixed to regular apartures located on vehicle's body load-bearing elements. In case of correct installation the skid plate should not interfer ewith any vehicle's units and components.

INSTALLATION MANUAL:

- Remove regular plastic duster.
- 2. Fix the skid plate's beam (1) to the radiator's beam
- 3. Fix the skid plate's beam (2) to apertures of the front axle beam's power elements.
- Fix the skid plate to the mounted parts.
- 5. Tighten all screw joints.

OPERATING CONDITIONS:

Engine bay and transmission elements skid plate has been designed to operate in conditions specified by whiche's producer. Cases of crush or driving into obstacles at a speed should be excluded during exploitation. In case of head-on crush it is necessary to assure in absence of damages of vehicle's components and units and availability of randwrithings and certified service stations.

WARRANTY:

Warranty period - 1 year.

WARRANTY TERMS:

WAKKAN BETTAKES

The skid plate should be installed on a vehicle with undamaged body and load-bearing elements (vehicle, which hads never been involved in mad traffic accident):

There are no mechanical damages of the skid plate resulting from head-on crush. All requirements to skid plate installation should be satisfied;


There are no mechanical damages of powder coating.

There are no mechanical damages of powder coating.

Producer does not bear liability for damages caused to the vehicle, health and life of people in case of installation and exploitation terms yieldston. Producer has a right to introduce changes into the skid plate construction.



The Quality Management System of LLC Metalloproduktsia has been audited by Bureau Veritas Certification and conforms to requirements of the ISO 9001:2008 standard.





Thread	M6x1.0	M8x1.25	M10x1.5	M12x1.75
ightening torque	9.8 Нм	24.0 Нм	47.0 Hm	81.0 Hm

Nut8