Engine bys and transmission elements side plate has been designed and manufactured by LLC Metallogonodation.

Product conforms to TOR 459-100-12888789-2008 requirements. Product design is protected by model copyright certificates Ne8090-1, 1980-1, 1981-1

Toyota

INSTALLATION MANUAL: 1. Fix straps to lateral apertures in 2. Fix the front part of the skid plate 3. Tighten all screw joints.

Fix straps to lateral apertures in the transmission bearing beam and fix the skid plate's beam to them.
 Fix the front part of the skid plate to the skid plate for engine bay, and the rear part-to mounted beam.

Installation manual

OPERATING CONDITIONS:

Engine bay and transmission elements skid plate has been designed to operate in conditions specified by whick's producer. Cases of crush or driving into obstacles at a speed should be excluded uniq exploitation. In case of head-on crush it is necessary to assure in absence of damages of vehicle's components and units and availability of conductations; on partified assure in a state of the conductations.

plate is fixed to regular apertures located on vehicle's body load-bearing elements. In case of correct installation the skid

WARRANTY: Warranty period - 1 year.

WARRANTY TERMS:

The skid plate should be installed on a vehicle with undamaged body and load-bearing elements (vehicle, which hads never been involved in road traffic accident); There are no mechanical damages of the skid plate resulting from head-on crush. All requirements to skid plate

installation should be satisfied; There are no mechanical damages of powder coating.

plate should not interfere with any vehicle's units and components.

There are no mechanical damages of powder coating. Producer does not bear liability for damages caused to the vehicle, health and life of people in case of installation and exploitation terms violation. Producer has a right to introduce changes into the skid plate construction.



The Quality Management System of LLC Metalloproduktsia has been audited by Bureau Veritas Certification and conforms to requirements of the ISO 9001:2008 standard.



LIST OF PARTS				
NO.	NAME	QTY.		
1	Rear beam	1		
2	Bolt M10x30	6		
3	Strap	2		

Skid plate for: transmission case and transfer box

vvasilei 10			
Thread	M6x1.0	M8x1.25	M10x1.5
Tighteeing termin	0.041	24.0 Non	47.0 11

Article: 24.0862/24.0863

4

M12x1.75